



**COLL**  
HEALTH AND SAFETY INC.  
15 - 145 Traders Blvd. East  
Mississauga, ON L4Z 3L3  
p: 905 625 3994 f: 905 625 6684  
t: 1.800.267.9317 e: bruce@collhealth.com  
w: www.collhealth.com

# TANKER TESTER GAS MONITOR

Gas Detection For Life

**EAGLE™ Model**



## Features

- Simultaneously monitor 100% LEL and volume of HC as well as O<sub>2</sub> and H<sub>2</sub>S
- Monitor HC gas from inerted tanks
- Auto-ranging display between % volume and % LEL
- Powerful long-life pump with 125' range with filters
- Low flow pump shut off and alarm
- Security "Adjustment Lockout Switch"
- Up to 30 hours of continuous operation
- Alkaline or Ni-Cad capability
- Datalogging option
- Autocalibration
- Dual hydrophobic filters
- Internal oil mist filter
- Ergonomic RFI / EMI / chemical / weather resistant enclosure
- Intrinsically safe design, CSA (C / US) & UL Classified

RKI is pleased to offer the most versatile portable gas detector specifically for maritime tankers. The EAGLE provides detection combinations never before offered in a portable gas monitor featuring gases like % LEL and volume of hydrocarbons, oxygen, as well as PPM levels of hydrogen sulfide.

The EAGLE features include an infrared sensor for combustible gas monitoring in inerted tanks, and dual hydrophobic filters to increase its water resistant performance. For quick response and recovery from distant sampling locations, the EAGLE has a strong internal pump with an adjustable low flow auto shut off and alarm, which can draw samples up to 125 feet even with the dual hydrophobic filters in place. The EAGLE will continuously operate for over 30 hours on alkaline batteries or 18 hours on Ni-Cads. A variety of accessories are also available to help satisfy almost any application such as long sample hoses, datalogging, continuous operation adapters, remote alarms and strobes, extra loud buzzer and alkaline recognition battery charger.

With its ergonomic design and large glove friendly buttons, the EAGLE offers easy access to controls such as autocalibration, alarm silence, demand zero, peak hold and a wide variety of other features and settings. Each channel has two alarm levels. The two alarm levels are user adjustable and can be latching or self resetting. Rugged, reliable, easy to operate and maintain, the EAGLE is the solution for testing HC vapor levels in inerted tanks. Also, it can detect H<sub>2</sub>S levels up to 1,000 ppm.

**RKI Instruments, Inc. 33248 Central Ave. Union City, CA 94587 • Phone (800) 754-5165 • (510) 441-5656 • Fax (510) 441-5650**

World Leader In Gas Detection & Sensor Technology  
www.rkiinstruments.com

# EAGLE™ Model

<b>Enclosure</b>	Weather and chemical resistant, RFI / EMI coated high impact poly-carbonate-polyester blend. Can operate in rain or set into 2.5" of water without damage. Ergonomically balanced with rugged top mounted handle.
<b>Dimensions</b>	10.5" L x 5.9" W x 7" H
<b>Weight</b>	5 lbs
<b>Detection Principle</b>	Electrochemical cell, galvanic cell, and infrared.
<b>Sensor Life</b>	2 years under normal conditions.
<b>Sampling Method</b>	Powerful, long-life pump (over 6,000 hours) can draw samples over 125 feet. Flow rate approximately 2.0 SCFH.
<b>Display</b>	4 x 20 LCD readout. Viewed through window in case top. Displays readings & status of all channels simultaneously. Backlight, automatic for alarms and by demand with adjustable time.
<b>Alarms</b>	2 alarms per channel. The two alarms are fully adjustable for levels, latching or self reset and silenceable.
<b>Alarm Method</b>	Buzzer 85 dB at 30 cm, dual high intensity LEDs, and flashing display.
<b>Controls</b>	6 external glove friendly push buttons for operation, demand zero, and autocalibration. Buttons also access alarm silence, peak hold, battery status and many other features.
<b>Continuous Operation</b>	30 hours minimum using alkaline batteries, or 18 hours using Ni-Cads.
<b>Power Source</b>	4 alkaline or Ni-Cad, size D batteries. Charger has alkaline recognition to prevent battery damage if charging is attempted with alkalines.
<b>Operating Temp. &amp; Humidity</b>	-10°C to 40°C (14°F to 104°F), 0 to 95% RH, non-condensing.
<b>Response Time</b>	30 seconds to 90% (for most gases) using standard 5 ft hose.
<b>Safety Rating</b>	Intrinsically Safe, Class I, Division 1, Groups A, B, C and D. CSA (C / US) & UL Classified.
<b>Standard Accessories</b>	Shoulder strap, alkaline batteries, hydrophobic probe and 5 foot hose, internal hydrophobic filter, and oil mist filter (internal)
<b>Optional Accessories</b>	<ul style="list-style-type: none"> <li>• Datalogging of up to 4 gases</li> <li>• Remote alarms</li> <li>• Ni-Cad batteries</li> <li>• Battery charger, 115 VAC, 220 VAC, or 12 VDC</li> <li>• Continuous operation adapter, 115 VAC or 12 VDC</li> <li>• Extra loud buzzer</li> <li>• Extension probes</li> </ul>
<b>Warranty</b>	One year material and workmanship

Ordering Information	
Part Number	Description
72-5354RK	HC (100% LEL / 30% Vol. autoranging IR) / O <sub>2</sub> / H <sub>2</sub> S (0-100ppm)
72-5355RK	HC (100% LEL / 30% Vol. autoranging IR) / O <sub>2</sub> / H <sub>2</sub> S (0-1,000ppm)
72-5268RK	HC (100% LEL / 30% Vol. autoranging IR) / O <sub>2</sub>

### Special Features

- Low flow alarm shuts pump off to avoid damage to instrument.
- Hydrophobic filter disc in probe.
- Internal hydrophobic filter.
- Single gas calibration capability.
- Methane elimination switch for environmental applications.
- Security "Adjustment Lockout Switch".
- Confirmation beep (silenceable).

Specifications subject to change without notice.



A9812



ISO 9001:2000

33248 Central Ave, Union City, CA 94587

Toll Free: (800) 754-5165 • Phone: (510) 441-5656 • Fax: (510) 441-5650  
 mail4rki@rkiinstruments.com • www.rkiinstruments.com

### Authorized Distributor:



15 - 145 Traders Blvd. East  
 Mississauga, ON L4Z 3L3  
 p: 905 625 3994 f: 905 625 6684  
 t: 1.800.267.9317 e: bruce@collhealth.com  
 w: www.collhealth.com